

Pro Start 16-24-10

A HIGH PHOSPHATE/CONTROLLED RELEASE PRE-PLANT(Starter) **DESCRIPTION:** FERTILIZER with X-Cote™ Polymer-Coated Sulfur-Coated Urea

BENEFITS: PRO START 16-24-10

- Contains a 2:3:1 ratio of N-P₂O₅-K₂O to provide high levels of phosphate for new plantings.
- Contains X-Cote[™], polymer-coated sulfur-coated urea, for extended release of nitrogen up to 10 weeks. Contains a BEST[®] Homogeneous Pellet for nutrient distribution, and virtually eliminating the chance of staining.
- Contains secondary and minor elements.

APPLICATION RATES:

AFFEIGATION NATES.	Pounds of Actual	Pounds of pro start	Pounds of pro start
	P ₂ O ₅ desired	to apply per	to apply per
	per 1,000 sq.ft.	1,000 sq.ft.	Acre
Turfgrass:	1.00	4.2	183
Recommended Rate	1.50	6.25*	272*
	2.00	8.4	366

Clay Soils - Broadcast 5 lbs. per 1,000 sq. ft. (218 lbs. per acre) Loam Soils - Broadcast 7 lbs. per 1,000 sq. ft. (305 lbs. per acre) Sandy Soils - Broadcast 9 lbs. per 1,000 sq. ft. (392 lbs. per acre)

TURFGRASS OVERSEEDING: Broadcast 6.25 lbs. per 1,000 sq. ft. (275 lbs. per acre).

GROUNDCOVER: Broadcast at 5 lbs. per 1,000 sq. ft. (.5 lbs. per 100 sq. ft.).

SHRUBS & EVERGREENS: Sprinkle 2/3 cup evenly around dripline of plant and work into top 1 inch of soil.

NOTE: Liquid measuring cups are very close in estimating the weight of dry granular fertilizers. Example: an 8 oz. (1 cup) measuring cup holds approximately 8 oz. of dry granular fertilizer.

PRODUCT COVERAGE:

Based on the Recommended Turfgrass Rate

SGN 250

ONE 50-LB. BAG COVERS 8,000 SQ.FT. 5½ - 50-LB. BAGS COVER 1 ACRE.



SPREADER SETTINGS:

SPINEADEN SETTINGS.			
Listed Settings Will	BEST® Pro	61/2B	Rates are for spreading
Approximately Apply the	Spyker / BEST® Models 34, 44, 64	5.2	one time across in one direction
Recommended Rate.	Earthway		-
	Lesco	Q	
	Scotts R-8A (Cone 5)	N½	
	Lely 1250 / Vicon	visit www.bestfertilizer.com	

NOTE: Spreader settings are guidelines only. Spreaders should be checked for accuracy.

APPLICATION PRECAUTIONS:

- Apply to dry turf or foliage and irrigate thoroughly immediately after application.
- Iron and other plant nutrients can cause staining of sidewalks. Sweep walkways prior to irrigation. Walkways should be dry at time of application.
- Keep away from pools, ponds, etc. Do not contaminate potable water.
- Do not apply with a drop-type spreader. The grinding action of these spreaders can damage the X-Cote™. coating and can increase turf burn potential.

GUARANTEED ANALYSIS:

TOTAL NITROGEN (N)	16.00%
8.50% Ammoniacal Nitrogen	
7.50% Urea Nitrogen*	
AVAILABLE PHOSPHATE (P,O,)	24.00%
SOLUBLE POTASH (K,O). L. SOLUBLE POTASH (K,O).	10.00%
Sulfur (S)	3.50%
Iron (Fè)	0.750/

Derived from Polymer-Coated Sulfur-Coated Urea, Diammonium Phosphate, Monoammonium Phosphate, Ammonium Sulfate, Sulfate of Potash, Muriate of Potash and Iron Oxysulfate.

*7.00% Slowly available urea nitrogen from polymer-coated sulfur-coated urea.

Information regarding the contents and levels of metals in this product is available on the Internet at http://www.regulatory-info-jr.com

PACKAGE SIZE: HANDLING PRECAUTIONS: **MSDS: See Reverse**

50-LB. (22.68-Kg.)BAGS CAUTION: KEEP OUT OF REACH OF CHILDREN HARMFUL IF SWALLOWED — DO NOT INHALE

74381_prostart162410_R1-15-2010



